

Tecnosicurezza Service Reset

Software instructions



Tecnosicurezza Service Reset

Company

Founded in 1983 with the aim of providing a complete range of professional products, Tecnosicurezza is now a consolidated reality in the field of locks and security systems for safes.

The experience gained in over 35 years of activity in the security sector has allowed the designing and manufacturing of high technology and reliability systems, which continue to receive the approval of an increasingly demanding clientele.

TECNOSICUREZZA is present directly all over the world through its own branches and with an extensive distribution network.

TECNOSICUREZZA is aimed at national and international customers of primary importance, such as banks, safe manufacturers, cash in transit companies, mass market retailers and post offices.

Today TECNOSICUREZZA is a leading company focused on the customers' needs and is constantly in step with technology.

Tecnosicurezza Service Reset

Table of contents

COMPANY	2
TABLE OF CONTENTS	3
1. OVERVIEW AND PRELIMINARY OPERATIONS	4
1.1 INSTALL THE USB INTERFACE	4
1.2 INSTALL TECNOSICUREZZA SERVICE RESET ON PC	4
2. TECNOSICUREZZA SERVICE RESET – MAIN TOOLBAR	4
3. SERVICE MESSAGE RESET PROCEDURE	5
CORRECT DISPOSAL OF THIS PRODUCT:	8
(WASTE ELECTRICAL & ELECTRONIC EQUIPMENT)	8
CONTACTS	8

Before operating the lock,
please read this manual thoroughly,
and retain it for future reference.

Tecnosicurezza Service Reset

1. Overview and preliminary operations

This software allows you to postpone the issue date of the maintenance request message on the keypad and lock. The time period to postpone this date and the message that the keypad must show, are always the same initially set through the TechMaster Setup software.

1.1 Install the USB interface





To use the software Service Reset, it is necessary to have the black USB interface (p.n. N42180/T) connected with the PC.

To be sure that the black USB interface is working properly, it is advisable to install its drivers as described in the user manual IU_Driver_Installation_XX, available in the section "Download" of the website (www.tecnosicurezza.it).

Once the driver has been installed, plug the USB interface into the PC.


1.2 Install Tecnosicurezza Service Reset on PC

This software is provided by Tecnosicurezza. To install it, proceed as follow:

1. Double click the file Tecnosicurezza_Service_Reset_x.x.x.exe.
2. Click "Yes" on the pop-up message that appears, this will allow the app to make changes in your device.
3. In the setup wizard click on  and accept the License agreement.
4. Select the folder where one wants to install the software and click on .
5. Select whether one wants to create a program's shortcuts in some Start menu folder and click on .
6. Click on  to begin the installation.
7. Once the installation has terminated, click on  to terminate.

2. Tecnosicurezza Service Reset – Main Toolbar

The software Tecnosicurezza Service Reset has a top toolbar that allows you to perform the following operations:



Tecnosicurezza Service Reset

Read To read the information of the connected keypad.

Reset To postpone the issue date of the maintenance request message.

Language To change the menu language.

About To view the software version and checks whether software updates are available.



To check whether the USB interface is correctly detected by the software (the *Port* field should not be empty, it must contain the USB interface ID).

Keypad version To view the keypad firmware version and keypad name.

Keypad date/time To view the current keypad date and time.

Service duration To view the service message duration, configured by TechMaster Setup.


Message row 1 To view the service message text configured by TechMaster Setup.

Message row 2

3. Service message reset procedure


To reset the service message, the following steps must be performed:

1. Connect the USB communicating interface either to the PC USB port and to the keypad jack socket (N42180/T and T42146/J).
2. Switch on the keypad by pressing any key and access to "PC LINK" function, inside master/manager menu.
3. Press : LCD shows the message "PC LINK...".
4. Click twice on icon  of Tecnosicurezza Service reset software for opening it. The following screen-view appears:




5. Click on "Read": few seconds later, the software shows the keypad firmware version, current date and time, service message duration and service message text on rows 1 and 2. A confirmation message for the operation is displayed as well.

Tecnosicurezza Service Reset



6. Click on "Reset": if successful, the software displays an operation confirmation message, together with the new expiry date for the service message. Click on "OK" to confirm and close the program by clicking on the right-top side.



7. If more locks are connected to the keypad, repeat the steps from 2 to 6 after selecting the desired lock.

Correct disposal of this product:

(Waste Electrical & Electronic Equipment)

Applicable in the European Union and other European countries with separate collection systems.



This marking displayed on the product or its literature indicates that it should not be disposed with other wastes at the end of its working life.

To prevent possible harm to the environment or human health from uncontrolled waste disposal, please separate this from other types of wastes and recycle it responsibly to promote the sustainable reuse of material resources.

Contacts

GLOBAL HEADQUARTERS

Tecnosicurezza SpA

Via Cesare Battisti, 276
37057 San Giovanni Lupatoto
Verona

Tel.+39 045 826 64 70

Fax. +39 045 826 64 69

info@tecnosicurezza.it

USA HEADQUARTERS

Tecnosicurezza Inc.

50, Thomas Lane
Versailles, KY 40383

Tel.+1 859 490 89 30

info@usatecno.com

SPAIN HEADQUARTERS

Tecnosicurezza Sa

C/Menor, 4 - Nave 10
Pol. Ind La Mina 28770
Colmenar Viejo

Tel.+34 91 804 33 91

Fax.+34 91 804 32 63

info@tecnosicurezza.es